

**AMENDMENTS TO THE CLAIMS**

**LISTING OF CLAIMS:**

1-6. (canceled).

7. (currently amended): A spatial light modulator comprising:

a support substrate that has an electrode layer; and

a movable thin film that has at least an electrode layer, said movable thin film being opposingly placed above said support substrate with being separated by a predetermined gap distance in a manner that said movable thin film is flexurally deformable toward said support substrate,

wherein a predetermined driving voltage is applied between said electrode layer of said support substrate and said electrode layer of said movable thin film to cause said movable thin film to be deflected toward said support substrate by an electrostatic force acting between said electrode layers, whereby optical characteristics of said device with respect to incident light are changed to perform light modulation on the incident light,

and wherein an optical functional film having a plurality of stacked films according to claim 1 is disposed on each of sides of said movable thin film and said support substrate, said sides being opposed to each other, and said optical characteristics are optical interference characteristics corresponding to the gap distance between said movable thin film and said support substrate, and a wavelength of the incident light,

wherein the plurality of stacked films are formed of SiNx, and refractive indices of adjacent ones of the plurality of films are different from each other, and

wherein stresses of prescribed ones of the plurality of films of the multilayer film have opposite signs with respect to adjacent ones of the plurality of films.

8. (previously presented): A spatial light modulator array wherein plural spatial light modulators according to claim 7 are arranged one- or two-dimensionally.

9. (previously presented): An image forming device comprising:

a light source;

a spatial light modulator array according to claim 7;

an illumination optical system which illuminates said spatial light modulator array with light from said light source; and

a projection optical system which projects light emitted from said spatial light modulator array onto an image forming face.

10. (previously presented): A flat panel display comprising:

a light source which emits ultraviolet rays;

a spatial light modulator array according to claim 7;

an illumination optical system which illuminates said spatial light modulator array with light from said light source; and

a fluorescent member which is excited by light emitted from said spatial light modulator array to emit light.

11. (new): The spatial light modulator of claim 7 wherein the plurality of stacked films of optical functional film are grown by chemical vapor deposition (CVD).